

Attenda®

4 Shelf Storage Unit



Fabrication & Material

Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, anti-ligature, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. ligature resistant design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

Warranty

10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.

Maintenance

For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/ water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation

Anchors required for permanently attaching to solid wall. Anchors not supplied by Norix. Groove along mounting surface for caulk application (caulk not supplied by Norix).

Patents

This product may be covered by US Patent No. US 8,007,059 B2 and Patent Pending.

Environmental Test Standards

- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards

- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

Model	ATN401
Weight	69 lbs / 31.3 kg

Dimensions	in	cm
Width	27"	68.6
Depth	13.8"	35.1
Height	68"	172.7
Cubby Volume	cu ft	m³
Single Cubby	1.4	0.03
Total Cubby Volume	5.7	0.16

*Note: Dimensional tolerances are +1% due to manufacturing process.

Finishes

See Design Guide for finish options.

Assembly

None required.

*Intended for indoor use only

